

TANGO Series 1 / 108 cell  
390W - 405W  
Monocrystalline PV Module  
Monofacial

The TANGO module uses Convalt's state-of-the-art cell cutting technology, and advanced module manufacturing experiences



**Key Features**




Positive power tolerance  
+0 ~ +5 watt



100% EL inline inspection  
Better module reliability



Withstands heavy loading  
front load 5400 Pa & rear load 2400 Pa



Designated for 1000 VDC  
Reduces the Balance of System  
effectively



Excellent low light performance  
3.5% relative eff. reduction at low light  
(200W/m<sup>2</sup>)



Self-cleaning  
effect



Salt mist  
resistance  
certified



Fire class A  
certified



Dust & Sand  
resistance



Ammonia  
resistance



### Electrical Data

Model - STC		CVLT390-108M-BB	CVLT395-108M-BB	CVLT400-108M-BB	CVLT405-108M-BB
Maximum Rating Power (Pmax)	[W]	390	395	400	405
Module Efficiency	[%]	19.98	20.23	20.49	20.75
Open Circuit Voltage (Voc)	[V]	36.84	37.03	37.20	37.36
Maximum Power Voltage	[V]	30.82	31.00	31.17	31.36
Short Circuit Current (Isc)	[A]	13.50	13.59	13.68	13.78
Maximum Power Current	[A]	12.66	12.75	12.84	12.92

\*Standard Test Condition (STC): Cell Temperature 25°C, Irradiance 1000 W/m<sup>2</sup>, AM 1.5  
 \*Values without tolerance are typical numbers. Measurement tolerance: ± 3%



### Mechanical Data

Item	Specification
Dimensions	1723 mm (L) <sup>1</sup> x 1133 mm (W) <sup>1</sup> x 35 mm (D) <sup>2</sup> / 67.83" (L) <sup>1</sup> x 44.61" (W) <sup>1</sup> x 1.38" (D) <sup>2</sup>
Weight	21.7 kg / 47.84 lbs
Solar Cell	12x9 pieces monocrystalline solar cells series strings
Front Glass	White toughened safety glass, 3.2mm thickness
Cell Encapsulation	EVA (Ethylene-Vinyl-Acetate)
Frame	Black anodized aluminum profile
Junction Box	IP≥ 68, 3 diodes
Cable & Connector	Potrait : 500 mm (cable length can be customized), 1 x 4 mm <sup>2</sup> compatible with MC4
Package Configuration	31 pcs per Pallet, 806 pcs per 40' HQ container

<sup>1</sup> : With assembly tolerance of ± 2 mm [ ± 0.08in]  
<sup>2</sup> : With assembly tolerance of ± 0.8 mm [ ± 0.03in]

### Operating Conditions


Item	Specification
Mechanical Load	5400 Pa
Maximum System Voltage	1000V
Series Fuse Rating	30 A
Operating Temperature	-40 to 85 °C

### Temperature Characteristics


Item	Specification
Nominal Module Operating Temperature	45°C ± 2°C
Temperature Coefficient of Isc	0.048 % / °C
Temperature Coefficient of Voc	-0.27 % / °C
Temperature Coefficient of Pmax	-0.32 % / °C

\*Nominal module operating temperature (NMOT): Air mass AM 1.5, irradiance 800W/m<sup>2</sup>, temperature 20°C, windspeed 1 m/s.  
 \*Reduction in efficiency from 1000W/m<sup>2</sup> to 200W/m<sup>2</sup> at 25°C: 3.5 ± 2%.


### Engineering Drawing (mm)



### Dependence on Irradiance



### Reliability with Warranty



For more information, please visit [www.convalt.com](http://www.convalt.com)

#### Convalt Manufacturing LLC

Subsidiary of Convalt Energy, Inc.

#### Manufacturing

Convalt Manufacturing LLC  
 Watertown, New York,  
 800 Starbuck Avenue, A-15,  
 Watertown, NY 13601, USA

#### Headquarters

Convalt Energy, Inc.  
 1185 Avenue of the Americas,  
 3rd Floor New York,  
 +1 (212) 683-0400  
[sales@convalt.com](mailto:sales@convalt.com)